

GRAVEL BASE HONEYCOMB STABILISERS (CORE DRIVE)

TECHNICAL SPECIFICATIONS

General:

- material: 100 % recycled or pure Polypropylene (recyclable)
- color: white, gray or black
- membrane: DuPont™ Typar® – 68 g/m²
- drainability EN ISO 11058: 180 L / (m².s)
- UV and frost: UV and frost resistant
- durability: predicted to be durable for more than 100 years in all natural soils with temperatures < 25 °C

Physical data:

- standard sheet size L x W x H: 1176 x 764 x 32 mm (0.9 m²)
- XXL sheet size L x W x H: 2292 x 1176 x 32 mm (2.7 m²)
- cell size: 42 mm diameter
- weight per m²: 1.53 Kg
- gravel volume or weight: 50 l/m² = 75 kg/m²
- vertical strength, empty: 120 T / m² (pure PP)
95 T / m² (100% recycled PP)
- vertical strength, filled: depending on gravel 250 – 450 T/m²



ROCK STAR CONSTRUCT SRL
Aleea Teisani nr137A Sector 1 Bucuresti
RO 22680005 | J40/20648/2007
RO79 BTRL 0500 1202 8671 45XX
BANCA TRANSILVANIA OTOPENI
office@piatraonline.ro www.piatraonline.ro

